

SEMI-AUTO STRAPPING MACHINE
KT-15



KINGTON
Automated Business Systems

Specification	
Sealing Technology	Welding & hot plate pressing sticking
Warm-up time	Zero. Immediately after switch on power
Strapping Size	Min: 2-1/2" Width x 1" Height, Max: No limit
Performance	Max upto 25 wrapping per minute
Tension Strength	5 ~ 40 kg (88.2lb Adjustable)
Power Supply	Single Phase AC 110V/60Hz or 220V/50Hz, 150 W
Dimension	545 (D) x 785 (W) x 750 (H) mm
Weight	N.W. 55 kgs (122lbs) ; G.W. 65 kgs
Max Loading weight	180 kg
Table height	Adjustable 720-870 mm
Available Tape Material	Polypropylene (P.P.), Tape Thickness: 0.55-0.7 mm
Strap Tape Size	Width: 5, 6, 9, 12, 15.5 mm, Length: 750, 1500, 2800m
Strapping Roll Size	8 x 8 inch

Optional

**Anti-Static & Conductive Tape**

Conductive PP band offers 10^5 ohms resistivity for fast static discharge and up to 170°C heat resistance—ideal for ESD protection and high-temp baking without deformation.

**Customizable Colored Tape**

Available in a wide range of colors — white, light blue, pink, gold, tawny, rouge, olive. Custom printing of customer logo, text is also supported. Colorful strapping enhances product presentation and value.

*Compact structure with reduced mechanical complexity. The above-mentioned specialty strapping bands are optional accessories and can be used with KT-15 Semi-automatic strapping machines.



KINGTON

Automated Business Systems

KINGTON CO., LTD.

5F, No. 194, Sec. 3, Datong Road,
Xizhi District, New Taipei City, Taiwan
TEL / FAX : 886-2-8662-6882

For more information,

