AUTOMATIC STRAPPING MACHINE

TA SERIES



Perfect for strapping 10 bundles (1,000 pcs) of banknotes. Conductive soft PP strapping band & anti-static PP soft band are ideal for bundling IC trays, opto-electronic blister boxes, panels, PCBs, and other fragile, static-sensitive products. Premium packaging has never been this easy and efficient!

KINGTON

Automated Business Systems

Specification	Sealing Technology	Welding & hot plate pressing sticking
	Warm-up time	Approx 30~60 second after switch on power
	Operating method	Automatic, Manual & Foot Switch
	Performance	Up to 20 bandings per minute
	Tension Strength	7 kg ~10.5 kg (Adjustable)
	Arch Size	360 (W) x 180 (H) mm
	Power Supply	Single Phase AC110V/60Hz or 220V/50Hz
	Power Consumption	135 W (25W Motor x 2)
	Dimension	300 (D) x 760 (W) x 406 (H) mm
	Weight	N.W. 20 kgs ; G.W. 23 kgs
	Available Tape Material	Polypropylene (P.P.), Antistatic PP, Conductive PP Band
	Available Tape	Width: 8mm, Length: 750m; Thickness: 0.35mm
	Application to	10bundles money, IC Trays banding

Optional

Anti-Static & Conductive Tape

Conductive PP band offers 10⁵ ohms resistivity for fast static discharge and up to 170°C heat resistance—ideal for ESD protection and high-temp baking without deformation.



Customizable Colored Tape

Available in a wide range of colors — white, light blue, pink, gold, tawny, rouge, olive. Custom printing of customer logo, text is also supported. Colorful strapping enhances product presentation and value.

*The above-mentioned specialty strapping bands are optional accessories and can be used with the Kington TA series automatic strapping machines.



KINGTON

Automated Business Systems

KINGTON CO., LTD.

5F, No. 194, Sec. 3, Datong Road, Xizhi District, New Taipei City, Taiwan

TEL / FAX: 886-2-8662-6882

For more information,

